



The industry's first wireless tabletop conference phone. MAX Wireless provides the flexibility to hold a conference call when and where it's most convenient – with no cables in the way.

MAX Wireless is a perfect fit for offices and small conference rooms, delivering outstanding audio clarity.

Superior Audio Performance

- + Distributed Echo Cancellation® effectively eliminates echo
- + Noise cancellation removes background noises from fans or HVAC systems
- + True full-duplex performance allows users to speak and listen at the same time without audio cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones provide 360° audio pickup
- + ClearEffect™ provides natural, full-sounding audio without requiring wideband on both ends

Wireless Capabilities

- + Turn any room into a conference room, even without a phone line
- + Wireless signal range allows use in multiple rooms without moving the base unit
- + Wireless design provides a clean look with no wires on tables or floors
- + 12 hours of talk time allows for lengthy conferences without recharging; 36 hours of standby time reduces recharging frequency; automatic power-save mode conserves battery life
- + Dual-function power supply/charger enables conferencing while charging
- + Digital spread-spectrum technology with 64-bit encryption ensures secure conferencing
- + Audible warnings signal when phone is out of range or needs charging
- + Phone paging button allows easy identification of phone's location

Ease of Use & Control

- + Simple plug-and-play functionality makes installation and configuration a snap
- + Field-upgradeable for easy access to latest features
- + Selectable ring tones
- + Features user-friendly, telephone-style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation
- + Both phones can be operated using the dial pad of either phone - dialing, mute, volume controls, etc



VENUES


Boardrooms

Small Conference Rooms

Huddle Rooms

Home Office

Any Room Without Phone Lines



MAX Wireless is a single conference phone that connects wirelessly to a base unit for use in any small room.

PRODUCT SPECIFICATIONS

Echo Cancellation

- Tail time: 60 ms x 3

Noise Cancellation

- Dynamic noise cancellation

Telephone Connection

- Analog PBX or PSTN line
- RJ-11C, -12 dBm nominal

Radio

- Standard DECT/DECT 6.0 (NA, Canada, LATAM)
- WDCT (EMEA, APAC)
- ETSI EN 300 175 1-9

Keypad

- Alphanumeric standard keypad

Loudspeaker

- Volume: 90 dBspl A weighted @ 1 ft
- Bandwidth: 200 Hz–3.3 kHz

Record Output

- Connector: 2.5 mm mono audio jack
- Impedance: <1000 ohms
- Bandwidth: 200 Hz–3.3 kHz
- Dynamic range: 60 dB
- THD <.01%

Certifications

- FCC part 15/ICES-003 Class A
- FCC part 15 Subpart C/RSS-210
- FCC part 68/IC CS-03
- CE
- UL Certified

Power

Phone Unit:

- Custom battery pack with nickel metal hydride batteries, 7.2 V 2200 mAh
- 12 hours continuous talk time (typical)
- 36 hours standby

Base Unit:

- Auto-adjusting power module;
- 100-240 VAC; 50/60Hz

- DECT: 300 ft to 400 ft (91-121 m)

- EU WDCT unit: 50 ft (15 m)

Note: these ranges depend on environmental factors and may vary. The EU unit has a shorter range due to regulatory restrictions on power output in the 2.4 GHz frequency band in the EU.

Environmental

- Operating temperature: 32–118° F (0–48° C)
- Storage temperature: 41–158° F (5–70° C)
- Operating humidity: 15 to 80%
- Storage humidity: 10 to 90%

Dimensions (W x D x H)

- Phone unit: 10.5" x 10.5" x 3"
- (26.7 cm x 26.7 cm x 7.6 cm)
- Base unit: 4.25" x 5.5" x 2.5"
- (10.8 cm x 14 cm x 6.4 cm)

Weight

- Phone unit: 2.7 lb (1.2 kg)
- Base unit: .6 lb (0.27 kg)
- Shipping:
- MAX Wireless: 10 lb (4.5 kg)

MAX Wireless Includes

- Wireless phone unit (2)
- Base unit (1)
- Battery pack (2)
- Power supply/charger (2)
- Power supply retainer (2)
- Telephone cable
- Documentation CD
- Quick start guide

Part Numbers

- 910-158-600 (NA, Canada, LATAM)
- 910-158-276 (EMEA)
- 910-158-406 (Singapore/HK)

SALES AND INQUIRIES

North America

Tel: +1 801.975.7200

TollFree: +1 800.945.7730

TechSales: +1 800.705.2103

Fax: +1 801.303.5711

sales@clearone.com

Europe

Tel: +1.800.945.7730

global@clearone.com

Middle East

Tel: +1.800.945.7730

global@clearone.com

Asia Pacific

Tel: +1.800.945.7730

global@clearone.com

Other Regions

Tel: +1.800.945.7730

global@clearone.com

Other product names may be registered trademarks of their respective owners who do not necessarily endorse ClearOne or ClearOne's products. All rights reserved. Information in this document subject to change without notice. © 2016 ClearOne.